



POLYCAB WIRES PVT. LTD.

Industrial Cables LP No. 05/2017-18 Dtd 1st November 2017

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT (FR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FR							
	45 Mtr.	Coils Per Box	90 Mtrs.	Coils Per Box	180 Mtrs. (Box Packing)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box
0.75	420	48	800	28			2665	10
1	550	36	1050	24	2100	12	3500	8
1.5	820	30	1560	16	3120	10	5200	6
2.5	1320	20	2515	12	5030	6	8385	4
4	1940	16	3700	8	7400	4	8220	4
6	2940	8	5600	6	11200	3	12445	3
10			9945	1			22100	1
16			15940	1			35420	1

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES – FLAME RETARDANT LOW SMOKE (FRLSH) /FLAME RETARDANT ZERO HALOGEN (FRZH) / LOW SMOKE ZERO HALOGEN (LSZH) / HALOGEN FREE FLAME RETARDANT (HFFR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FRLS				HFFR/FRZH/LSZH	
	180 Mtrs. (Box Packing)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box
0.75			2800	10	2880	10
1	2205	12	3675	8	3780	8
1.5	3275	10	5460	6	5615	6
2.5	5280	6	8805	4	9055	4
4	7770	4	8630	4	8880	4
6	11760	3	13065	3	13440	3
10			23205	1	23870	1
16			37190	1	38255	1

Notes

1. The above rates are exclusive of GST which shall be charged extra.
2. This Price List is subject to change without notice.
3. As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.